

Document Scanners

fi-5015C



- 15 ppm colour (150 dpi) / black and white (200 dpi)
- 50-sheet A4 automatic document feeder
- A4 format flatbed for scanning delicate or bound documents
- Scan to print, scan-to-email, scan-to-SharePoint, scan-to-FTP, scan to network share, or to image / PDF viewer
- ABBYY FineReader OCR text recognition software included
- Adobe Acrobat 9.0 Standard included
- ScandAll PRO V2 included – professional batch scanning

Speed and flexibility

Fujitsu's fi-5015C simplifies day-to-day office work by making everyday workflows more efficient. The key feature of this desktop scanner is its intuitive operation and seamless integration into existing document management applications. The fi-5015C can be activated from a programmable control panel, allowing functions including Scan-to-File, Scan-to-Fax, Scan-to-Print and Scan-to-Email to be performed at the push of a button. Direct transfer to the text recognition program ABBYY® FineReader 8.0 Professional (included with the package) is also possible. This allows individual workers to save more time and use the original paper-based information more efficiently with the data being permanently stored in digital form.

The fi-5015C offers a scanning speed of up to 15 black and white pages per minute (simplex) at a resolution of 150 dpi or 15 colour documents per minute at a resolution of 200 dpi. The automatic document feeder (ADF) also helps to ensure an efficient workflow and with a capacity of 50 sheets, it enables unsupervised scanning of multi-page document stacks.

Additionally an A4 format flatbed allows for scanning sensitive or historically valuable documents, photographic material, magazines or bound documents.

Document capture – quick and easy

The fi-5015C model provides outstanding image quality in black and white, grayscale and full colour with an optical resolution of up to 600 dpi. The scanner can automatically create graphic formats such as TIFF or JPEG, depending on the task, alternatively, you can choose PDF format, which has become the de facto standard for easy and reliable document exchange.

The full version of Adobe® Acrobat® 9.0 Standard which is included supports the addition of comments, digital signatures and fast electronic transfer of captured documents. Integrated hardware functions allow the user to control image improvement functions directly using the TWAIN and ISIS™ drivers supplied. Functions such as image enhancement, fault control, automatic removal of moiré patterns and colour screening improve the optical image quality automatically, freeing the user completely from time consuming post-processing of images.

Even better batch scanning performance is possible with the bundled ScandAll PRO V2 scanning software, which features embedded zonal OCR functionality, multi-streaming options and a wealth of output format including password protected PDF and PDF/A formats. In daily operation tasks the user can be supported by setting up job routine profiles that can easily be ex- and imported by multiple scan stations.

fi-5015C Specifications



50 Sheets

600 dpi

Simplex
15 ppm



ENERGY STAR®
compliant



"Adobe", "Acrobat" and the Adobe PDF logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Model		fi-5015C
Scanner type	ADF (automatic document feeder) and Flatbed, Double feed monitoring: paper length	
Scanning method	Simplex, Colour / Grayscale / Mono	
Image sensor	Colour CCD sensors	
Light source	White cold cathode discharge tube	
Document format	ADF	Maximum: 216 x 356 mm
	ADF	Minimum: 115 x 140 mm
	Flatbed	Maximum: 216 x 297 mm
Paper weight (unlimited for flat bed)	52 g/m ² to 127 g/m ²	
Scanning speed (JPEG / A4 portrait)	15 ppm (Simplex)	
	ADF: Colour / Grayscale / Mono (150 dpi)	
	Flatbed: Colour / Grayscale / Mono	Approx. 5.3 seconds (150 dpi)
Document feed capacity	50 sheets (A4: 80 g/m ²)	
Background colours	White	
Optical resolution	600 dpi	
Output resolution	50 to 600 dpi (in 1 dpi increments)	
Output format	Binary 1 bit, grayscale 8 bit, colour 24 bit	
AD converter (internal)	1024 levels	
Interfaces	High Speed USB 2.0	
Output mode (half tone)	Dither	
Voltage range	100 to 240 V AC, 50/60 Hz	
Current consumption	Operation max. 24W, power saving mode max. 6W	
Operating conditions	Temperature 5°C-35°C, Relative Humidity: 10%-85%	
Dimensions (W x D x H, base unit)	332 x 445 x 179 mm	
Weight	5.5 kg	
Drivers included in package	TWAIN, ISIS™	
Environmental compliance	ENERGY STAR® and RoHS	
Miscellaneous	Double feed detection	
Package includes	fi-5015C, Quick Installation or "Getting Started" Guide, Manual (book and CD), USB lead, mains adapter, driver CD (TWAIN and ISIS™ drivers for Windows) ScandAll PRO V2 for Windows image capture software, full version of Adobe® Acrobat® 9.0 Standard, full version of ABBYY® Fine Reader Professional 8.0, Quick Scan Pro Demo (Trial), Soft IPC (Trial)	

Options	Part number	Remarks
ScandAll PRO V2 Premium	PA43404-A283	ScandAll PRO V2 Premium upgrade

Consumables and Cleaning	Part number	Remarks
Pick Roller	PA03209-0551	Lifetime: Every 100,000 sheets or one year. These rollers feed documents into the scanner.
Pad Assembly	PA03209-0550	Lifetime: Every 50,000 sheets or one year. These rubber parts separate documents.
Cleaning kit	SC-CLE-WGD	72 x F1 Cleaning Fluid Impregnated Cleaning Wipes.
Consumable kit	CON-3209-009A	Includes: 1 x Pick Roller, 5 x Pad Assembly

Warranty and Service Plans	Remarks
Standard Warranty	1 year Advance Exchange within 1-2 days; Hotline and Online support; parts, labour and shipping included
Upgrade Options	1-5 year upgrades available on new scanners at time of scanner purchase or within 30 days of purchase, upgrades the warranty
Renewal Options	1-2 year renewals available when warranty or previous service plan has expired
Visit http://emea.fujitsu.com/assurance for further information on standard warranty and our Bronze, Silver, Gold and Platinum upgrade options.	

All names, manufacturer names, brand and product designations are subject to special trademark rights and are manufacturer's trademarks and/or registered brands of their respective owners. All indications are non-binding. Technical data is subject to change without prior notification.

PFU Imaging Solutions

Europe Limited
Hayes Park Central
Hayes End Road, Hayes
Middlesex UB4 8FE
England
Tel: (+44-(0)20) 8573 4444
Fax: (+44-(0)20) 8573 2643

PFU Imaging Solutions GmbH

Frankfurter Ring 211
80807 Munich
Germany
Tel: (+49-(0)89) 32378-0
Fax: (+49-(0)89) 32378-100

PFU Imaging Solutions S.p.A.

Via Nazario Sauro, 38
20099 Sesto San Giovanni (MI)
Italy
Tel: (+39) 0226294.1
Fax: (+39) 0226294.201

<http://emea.fujitsu.com/scanners>

FUJITSU